

Description

CONNECSYS 62.5/125µm OM1 multimode fiber is a graded-index multimode optical fiber with a 62.5µm core diameter and a 125µm cladding diameter. The optical fiber is comprehensively optimized for the performance at the 850nm and 1300nm operating wavelengths, which complies with the IEC 793-2 Type A1b Optical Fiber Specification. With the optical fiber low attenuation and high bandwidth, it overfills the transmission demand of IEEE 802.3z Gigabit Ethernet.

Characteristics	Conditions	Specified Values
Optical Characteristics		
Attenuation	850 nm	≤ 2.7 dB/km
	1300 nm	≤ 0.6 dB/km
Minimum Modal Bandwidth	850 nm	200 MHz•km
	1300 nm	600 MHz•km
Numerical Aperture		0.275 ± 0.015
Zero Dispersion Wavelength		1320 – 1365 nm
Zero Dispersion Slope		≤ 0.097 ps/(nm ² • km)
Group Index of Refraction	850 nm	1.496
	1300 nm	1.491
Backscatter Characteristics		
@ 1300 nm		
Step (Bidirectional Measurement)		≤ 0.10 dB
Irregularities Over Fiber Length And Point Discontinuity		≤ 0.10 dB
Attenuation Uniformity		≤ 0.10 dB/km
Geometrical Characteristics		
Core Diameter		62.5 ± 2.5 µm
Cladding Diameter		124.8 ± 1.0 µm
Cladding Non-Circularity		≤ 1.0 %
Coating Diameter		245 ± 7 µm
Coating – Cladding Concentricity Error		≤ 12.0 µm
Coating Non-Circularity		≤ 6.0 %
Core – Cladding Concentricity Error		≤ 1.5 µm
Environmental Characteristics		
@ 850 nm & 1300 nm		
Temperature Dependence Induced Attenuation at		-60°C to +85°C ≤ 0.10 dB/km
Temperature - Humidity Cycling Induced Attenuation at		-10°C to +85°C, 98% RH ≤ 0.10 dB/km
Water Soak Dependence Induced Attenuation at		23°C, for 30 Days ≤ 0.10 dB/km
Damp Heat Dependence Induced Attenuation at		85°C & 85% RH, 30 Days ≤ 0.10 dB/km
Dry Heat Aging at		85°C ≤ 0.10 dB/km
Mechanical Specifications		
Proof Test	Off Line	≥ 9.0 N; ≥ 1.0 %; ≥ 100 kpsi
Macro – Bend Induced Attenuation		
100 Turns Around a Mandrel of 60 mm Diameter	850 nm & 1300 nm	≤ 0.50 dB
Coating Strip Force	Typical Average Force	1.5 N
	Peak Force	≥ 1.3 N ≤ 8.9 N
Dynamic Stress Corrosion Susceptibility Parameter nd		≥ 27 nd

All Rights Reserved.

Although Zog Connecsyz Sdn. Bhd. ("CONNECSYS") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

CONNECSYS provides information and specifications herein on an "AS IS" basis, with no representations and warranties, whether express, statutory or implied. In no event will CONNECSYS be liable for any damage (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if CONNECSYS has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of CONNECSYS products are subject to CONNECSYS's standard terms and conditions of sale.

Note – this tech data is subject to change without notice.